



CT182T
PERFORMANCE TABLES



**CT182T**

Cruise Performance

Pressure Altitude Sea Level

Conditions:

3100 Pounds

Recommended Lean Mixture

Cowl Flaps CLOSED

RPM	MP	20°C BELOW STANDARD TEMP -5°C			STANDARD TEMPERATURE 15°C			20°C ABOVE STANDARD TEMP 35°C		
		% MCP	KTAS	GPH	% MCP	KTAS	GPH	% MCP	KTAS	GPH
2400	28	88	139	18.4	83	139	16.8	78	138	15.4
	26	81	134	16.2	76	134	14.9	72	133	13.8
	24	74	130	14.3	70	129	13.4	66	128	12.5
	22	65	123	12.4	62	122	11.7	58	121	11.1
2300	20	57	115	10.9	54	114	10.4	50	113	9.9
	28	87	138	16.9	82	138	15.7	77	137	14.5
	26	79	133	15.1	75	133	14.0	70	132	13.1
	24	72	128	13.5	68	128	12.7	64	126	11.9
2200	22	63	121	11.7	59	120	11.1	56	118	10.5
	20	55	114	10.5	52	113	10.0	49	111	9.5
	28	85	137	15.7	80	137	14.7	75	136	13.8
	26	77	132	14.1	73	132	13.2	68	130	12.4
2100	24	70	127	12.7	66	126	12.0	62	125	11.4
	22	60	118	11.0	56	117	10.5	53	116	10.0
	20	54	112	10.1	51	111	9.6	48	109	9.2
	18	46	104	8.9	44	102	8.5	41	98	8.1
2000	28	81	134	14.7	76	134	13.7	72	133	12.9
	26	73	129	13.1	69	129	12.4	65	127	11.7
	24	66	124	11.9	63	123	11.3	59	122	10.7
	22	58	116	10.5	54	115	10.0	51	113	9.5
2000	20	51	110	9.6	48	108	9.1	45	106	8.7
	18	44	100	8.4	41	98	8.1	39	94	7.7
2000	28	77	132	13.7	73	132	12.9	68	130	12.1
	26	69	126	12.3	66	126	11.7	62	124	11.0
	24	63	121	11.2	59	120	10.7	56	118	10.1
	22	56	114	10.1	52	113	9.6	49	111	9.2
2000	20	49	107	9.1	46	105	8.7	43	102	8.3
	18	41	97	8.0	39	94	7.6	37	90	7.2

NOTE

- For best economy, operate at peak T.I.T.
- Power settings not approved for cruising are indicated by dashes.



Cruise Performance

Pressure Altitude 2000 Feet

Conditions:

3100 Pounds

Recommended Lean Mixture

Cowl Flaps CLOSED

RPM	MP	20°C BELOW STANDARD TEMP -9°C			STANDARD TEMPERATURE 11°C			20°C ABOVE STANDARD TEMP 31°C		
		% MCP	KTAS	GPH	% MCP	KTAS	GPH	% MCP	KTAS	GPH
2400	28	---	---	---	84	142	17.1	79	142	15.7
	26	83	138	16.6	78	138	15.3	73	137	14.1
	24	76	133	14.7	71	133	13.7	67	131	12.8
	22	67	127	12.8	63	126	12.0	60	124	11.3
	20	59	119	11.2	56	118	10.7	52	116	10.2
2300	28	88	141	17.2	83	141	15.9	78	141	14.8
	26	81	136	15.4	76	136	14.3	71	135	13.3
	24	74	132	13.8	69	131	12.9	65	130	12.1
	22	65	124	12.0	61	124	11.4	57	122	10.8
	20	57	118	10.8	54	116	10.2	51	114	9.7
2200	28	86	140	15.9	81	140	14.9	76	139	13.9
	26	78	135	14.3	74	135	13.4	69	133	12.6
	24	71	130	13.0	67	129	12.2	63	128	11.6
	22	62	122	11.4	58	121	10.8	55	120	10.3
	20	55	116	10.3	52	114	9.8	49	112	9.4
2100	18	48	107	9.2	45	105	8.8	43	102	8.4
	28	82	137	14.8	77	137	13.9	73	136	13.0
	26	74	132	13.3	70	132	12.5	66	130	11.8
	24	67	127	12.1	64	126	11.5	60	125	10.9
	22	59	120	10.8	56	119	10.3	53	117	9.8
2000	20	53	113	9.8	50	111	9.3	47	109	8.9
	18	45	104	8.7	43	101	8.3	40	98	7.9
	28	78	135	13.9	73	134	13.0	69	133	12.3
	26	71	129	12.5	67	129	11.8	63	127	11.2
	24	64	124	11.4	60	123	10.8	57	121	10.3
	22	57	117	10.3	54	116	9.8	50	114	9.3
	20	50	110	9.3	47	108	8.9	44	105	8.4
	18	43	100	8.2	40	97	7.8	38	93	7.4

NOTE

- For best economy, operate at peak T.I.T.
- Power settings not approved for cruising are indicated by dashes.

**CT182T**

Cruise Performance

Pressure Altitude 4000 Feet

Conditions:

3100 Pounds

Recommended Lean Mixture

Cowl Flaps CLOSED

RPM	MP	20°C BELOW STANDARD TEMP -13°C			STANDARD TEMPERATURE 7°C			20°C ABOVE STANDARD TEMP 27°C		
		% MCP	KTAS	GPH	% MCP	KTAS	GPH	% MCP	KTAS	GPH
2400	28	---	---	---	86	145	17.5	80	145	16.0
	26	84	141	17.1	79	141	15.7	75	140	14.4
	24	77	137	15.1	73	136	14.0	68	135	13.0
	22	69	130	13.2	65	129	12.4	61	128	11.6
	20	61	123	11.6	57	122	11.0	54	120	10.5
2300	28	---	---	---	84	144	16.2	79	144	15.0
	26	82	140	15.7	77	140	14.6	72	138	13.6
	24	75	135	14.1	71	134	13.2	66	133	12.4
	22	67	128	12.4	63	127	11.7	59	126	11.1
	20	59	121	11.0	56	120	10.5	52	118	10.0
2200	28	87	143	16.1	82	143	15.1	77	142	14.1
	26	79	138	14.5	75	138	13.6	70	136	12.8
	24	72	133	13.2	68	132	12.4	64	131	11.7
	22	64	126	11.7	61	125	11.2	57	124	10.6
	20	57	119	10.5	53	118	10.0	50	115	9.6
2100	18	50	111	9.5	47	109	9.1	44	106	8.6
	28	83	140	15.0	78	140	14.1	73	139	13.1
	26	75	135	13.5	71	135	12.7	67	133	12.0
	24	69	130	12.3	65	129	11.6	61	128	11.0
	22	61	123	11.1	58	122	10.5	54	120	10.0
2000	20	54	116	10.0	51	114	9.5	48	112	9.1
	18	47	107	8.9	44	105	8.5	42	101	8.1
	28	79	137	14.0	74	137	13.1	70	136	12.4
	26	72	132	12.7	68	132	12.0	63	130	11.3
	24	65	127	11.6	61	126	11.0	57	124	10.4
2000	22	58	120	10.5	55	119	10.0	51	117	9.5
	20	51	113	9.5	48	111	9.0	46	108	8.6
	18	44	103	8.4	42	100	8.0	39	96	7.6

NOTE

- For best economy, operate at peak T.I.T.
- Power settings not approved for cruising are indicated by dashes.



Cruise Performance

Pressure Altitude 6000 Feet

Conditions:

3100 Pounds

Recommended Lean Mixture

Cowl Flaps CLOSED

RPM	MP	20°C BELOW STANDARD TEMP -17°C			STANDARD TEMPERATURE 3°C			20°C ABOVE STANDARD TEMP 23°C		
		% MCP	KTAS	GPH	% MCP	KTAS	GPH	% MCP	KTAS	GPH
2400	28	---	---	---	86	149	17.7	81	148	16.2
	26	85	144	17.3	80	144	15.9	75	143	14.6
	24	78	140	15.4	74	139	14.2	69	138	13.2
	22	70	134	13.5	66	133	12.6	62	131	11.9
	20	62	126	11.8	59	125	11.2	55	123	10.7
2300	28	---	---	---	85	147	16.3	79	147	15.1
	26	83	143	15.9	78	143	14.8	73	141	13.7
	24	76	138	14.3	72	137	13.4	67	136	12.5
	22	68	132	12.7	64	131	12.0	60	129	11.3
	20	60	124	11.3	57	123	10.7	53	121	10.2
2200	28	88	146	16.3	83	146	15.2	78	145	14.2
	26	80	141	14.7	75	141	13.8	71	139	12.9
	24	73	136	13.4	69	135	12.6	65	134	11.9
	22	66	130	12.0	62	129	11.4	58	127	10.8
	20	58	122	10.7	55	121	10.2	51	118	9.7
2100	18	51	114	9.7	48	112	9.3	45	109	8.8
	28	83	143	15.1	79	143	14.2	74	142	13.2
	26	76	138	13.7	72	138	12.9	68	136	12.1
	24	70	133	12.4	66	132	11.8	62	130	11.2
	22	62	126	11.3	59	125	10.7	55	123	10.2
2000	20	55	119	10.2	52	117	9.7	49	114	9.2
	18	48	110	9.1	46	108	8.7	43	104	8.3
	28	79	140	14.1	74	140	13.2	70	138	12.4
	26	72	135	12.8	68	134	12.1	64	133	11.4
	24	66	129	11.7	62	128	11.1	58	127	10.5
2000	22	59	123	10.6	56	122	10.1	52	119	9.6
	20	52	116	9.6	49	114	9.2	46	110	8.7
	18	45	106	8.6	43	103	8.2	40	98	7.8

NOTE

- For best economy, operate at peak T.I.T.
- Power settings not approved for cruising are indicated by dashes.



Cruise Performance

Pressure Altitude 8000 Feet

Conditions:

3100 Pounds

Recommended Lean Mixture

Cowl Flaps CLOSED

RPM	MP	20°C BELOW STANDARD TEMP -21°C			STANDARD TEMPERATURE -1°C			20°C ABOVE STANDARD TEMP 19°C		
		% MCP	KTAS	GPH	% MCP	KTAS	GPH	% MCP	KTAS	GPH
2400	28	---	---	---	86	152	17.8	81	151	16.2
	26	85	147	17.3	80	147	15.9	75	146	14.6
	24	79	143	15.5	74	142	14.4	70	141	13.3
	22	71	137	13.7	67	136	12.8	63	134	12.0
	20	63	129	12.0	60	128	11.3	56	126	10.8
2300	28	---	---	---	85	150	16.4	80	150	15.2
	26	83	146	15.9	78	145	14.8	73	144	13.8
	24	77	141	14.5	72	140	13.5	68	139	12.6
	22	69	135	12.9	65	134	12.1	61	132	11.4
	20	61	127	11.4	58	126	10.9	54	123	10.3
2200	28	88	149	16.3	83	149	15.3	78	148	14.2
	26	81	144	14.8	76	144	13.9	71	142	13.0
	24	74	139	13.5	70	138	12.7	66	137	12.0
	22	67	132	12.2	63	132	11.5	59	130	10.9
	20	59	125	10.9	56	124	10.4	52	121	9.9
2100	18	52	117	9.9	49	115	9.4	46	111	9.0
	28	84	146	15.2	79	146	14.2	74	145	13.3
	26	77	141	13.8	72	140	12.9	68	139	12.2
	24	70	136	12.6	66	135	11.9	62	133	11.2
	22	63	129	11.4	60	128	10.8	56	126	10.3
2000	20	56	122	10.3	53	120	9.8	50	117	9.3
	18	49	113	9.3	46	110	8.9	44	106	8.4
	28	79	143	14.1	75	142	13.3	70	141	12.5
	26	73	138	12.9	69	137	12.2	64	135	11.5
	24	66	132	11.8	62	131	11.2	59	129	10.6
2000	22	60	126	10.7	56	125	10.2	53	122	9.7
	20	53	118	9.7	50	116	9.3	47	113	8.8
	18	46	109	8.7	44	106	8.3	41	101	7.9

NOTE

- For best economy, operate at peak T.I.T.
- Power settings not approved for cruising are indicated by dashes.

**CT182T**

Cruise Performance

Pressure Altitude 10,000 Feet

Conditions:

3100 Pounds

Recommended Lean Mixture

Cowl Flaps CLOSED

RPM	MP	20°C BELOW STANDARD TEMP -25°C			STANDARD TEMPERATURE -5°C			20°C ABOVE STANDARD TEMP 15°C		
		% MCP	KTAS	GPH	% MCP	KTAS	GPH	% MCP	KTAS	GPH
2400	28	---	---	---	87	155	17.8	81	154	16.2
	26	85	150	17.3	80	150	15.9	75	148	14.7
	24	79	146	15.7	75	145	14.5	70	144	13.4
	22	72	140	13.9	68	139	13.0	64	137	12.2
	20	64	132	12.2	60	131	11.5	57	128	10.9
2300	28	---	---	---	85	154	16.4	80	152	15.2
	26	83	149	16.0	78	148	14.9	74	147	13.8
	24	77	144	14.6	73	143	13.6	68	142	12.8
	22	70	138	13.1	66	137	12.3	62	135	11.6
	20	62	130	11.6	59	129	11.0	55	126	10.4
2200	28	88	152	16.4	83	152	15.3	78	151	14.3
	26	81	147	14.9	76	146	14.0	72	145	13.1
	24	75	142	13.6	71	141	12.9	66	140	12.1
	22	68	135	12.3	64	135	11.7	60	133	11.1
	20	60	128	11.1	57	127	10.5	53	124	10.0
	18	53	120	10.0	50	118	9.6	47	114	9.1
2100	28	84	149	15.2	79	149	14.3	74	147	13.3
	26	77	144	13.9	73	143	13.0	68	142	12.2
	24	71	138	12.7	67	138	12.0	63	136	11.3
	22	64	132	11.5	60	131	11.0	57	128	10.4
	20	57	125	10.4	54	122	9.9	50	119	9.4
	18	50	116	9.4	47	113	9.0	45	109	8.6
2000	28	79	146	14.1	75	145	13.3	70	144	12.5
	26	73	140	13.0	69	139	12.2	65	138	11.5
	24	67	135	11.9	63	134	11.3	59	132	10.6
	22	60	129	10.9	57	127	10.3	54	124	9.8
	20	54	121	9.8	51	118	9.4	48	115	8.9
	18	47	111	8.8	44	108	8.4	42	103	8.0

NOTE

- For best economy, operate at peak T.I.T.
- Power settings not approved for cruising are indicated by dashes.



Cruise Performance

Pressure Altitude 12,000 Feet

Conditions:

3100 Pounds

Recommended Lean Mixture

Cowl Flaps CLOSED

RPM	MP	20°C BELOW STANDARD TEMP -29°C			STANDARD TEMPERATURE -9°C			20°C ABOVE STANDARD TEMP 11°C		
		% MCP	KTAS	GPH	% MCP	KTAS	GPH	% MCP	KTAS	GPH
2400	28	---	---	---	87	158	17.8	81	156	16.2
	26	85	153	17.3	80	152	15.9	75	151	14.6
	24	79	148	15.7	75	148	14.5	70	146	13.5
	22	73	143	14.0	69	142	13.1	65	140	12.3
	20	64	135	12.2	61	134	11.6	57	131	11.0
2300	28	---	---	---	85	156	16.4	80	155	15.2
	26	83	151	16.0	78	151	14.9	74	149	13.8
	24	77	146	14.6	73	145	13.6	68	144	12.7
	22	70	140	13.1	66	139	12.3	62	138	11.6
	20	62	133	11.6	59	131	11.0	55	128	10.5
2200	28	88	155	16.3	83	155	15.3	78	153	14.2
	26	81	150	14.8	76	149	13.9	72	147	13.1
	24	74	144	13.6	70	143	12.8	66	142	12.0
	22	67	138	12.3	64	137	11.6	60	134	11.0
	20	60	130	11.1	57	128	10.5	53	125	10.0
	18	54	122	10.1	50	119	9.6	47	115	9.1
2100	28	84	152	15.2	79	151	14.2	74	150	13.3
	26	77	146	13.8	73	145	13.0	68	144	12.2
	24	71	141	12.6	67	140	11.9	63	138	11.3
	22	64	134	11.5	60	133	10.9	57	130	10.4
	20	57	127	10.4	54	124	9.9	51	121	9.5
	18	50	118	9.5	48	114	9.0	45	110	8.6
2000	28	79	148	14.1	75	147	13.3	70	146	12.5
	26	73	143	12.9	69	142	12.2	65	140	11.5
	24	67	137	11.9	63	136	11.3	59	133	10.6
	22	60	131	10.9	57	129	10.3	54	126	9.8
	20	54	122	9.9	51	120	9.4	48	116	9.0
	18	47	113	8.9	45	109	8.5	42	104	8.1

NOTE

- For best economy, operate at peak T.I.T.
- Power settings not approved for cruising are indicated by dashes.

**CT182T**

Cruise Performance

Pressure Altitude 14,000 Feet

Conditions:

3100 Pounds

Recommended Lean Mixture

Cowl Flaps CLOSED

RPM	MP	20°C BELOW STANDARD TEMP -33°C			STANDARD TEMPERATURE -13°C			20°C ABOVE STANDARD TEMP 7°C		
		% MCP	KTAS	GPH	% MCP	KTAS	GPH	% MCP	KTAS	GPH
2400	28	---	---	---	87	160	17.8	81	159	16.2
	26	85	155	17.2	80	155	15.8	75	153	14.6
	24	80	151	15.8	75	150	14.6	71	149	13.5
	22	73	145	14.1	69	144	13.2	65	143	12.3
	20	65	137	12.3	61	136	11.6	57	133	11.0
2300	28	---	---	---	85	159	16.4	80	157	15.2
	26	83	154	15.9	78	153	14.8	73	152	13.8
	24	77	149	14.6	73	148	13.6	68	147	12.7
	22	70	143	13.2	66	142	12.4	62	140	11.6
	20	63	135	11.7	59	133	11.1	55	130	10.5
2200	28	88	158	16.3	83	157	15.2	78	156	14.2
	26	81	152	14.8	76	151	13.9	72	150	13.0
	24	74	146	13.5	70	145	12.7	66	144	12.0
	22	67	140	12.3	63	139	11.6	60	136	11.0
	20	60	132	11.1	57	130	10.5	53	126	10.0
	18	54	124	10.1	51	121	9.6	48	116	9.2
2100	28	83	154	15.1	79	153	14.2	74	152	13.2
	26	77	148	13.8	72	148	12.9	68	146	12.2
	24	70	143	12.6	66	142	11.9	62	140	11.3
	22	64	136	11.5	60	135	10.9	57	132	10.4
	20	57	128	10.5	54	126	10.0	51	122	9.5
	18	51	119	9.5	48	116	9.1	45	111	8.6
2000	28	79	150	14.1	74	150	13.2	70	148	12.4
	26	73	145	12.9	69	144	12.2	64	142	11.5
	24	67	139	11.9	63	138	11.3	59	135	10.6
	22	60	133	10.9	57	130	10.3	54	127	9.8
	20	54	124	9.9	51	121	9.4	48	117	9.0
	18	48	114	9.0	45	110	8.5	42	104	8.1

NOTE

- For best economy, operate at peak T.I.T.
- Power settings not approved for cruising are indicated by dashes.

**CT182T**

Cruise Performance

Pressure Altitude 16,000 Feet

Conditions:

3100 Pounds

Recommended Lean Mixture

Cowl Flaps CLOSED

RPM	MP	20°C BELOW STANDARD TEMP -37°C			STANDARD TEMPERATURE -17°C			20°C ABOVE STANDARD TEMP 3°C		
		% MCP	KTAS	GPH	% MCP	KTAS	GPH	% MCP	KTAS	GPH
2400	28	---	---	---	---	---	---	---	---	---
	27	88	161	18.2	83	160	16.7	78	159	15.3
	26	84	158	17.1	80	157	15.7	75	156	14.5
	24	80	154	15.8	75	153	14.6	71	151	13.5
	22	73	148	14.2	69	147	13.2	65	145	12.4
	20	65	140	12.4	61	138	11.7	58	135	11.0
2300	28	---	---	---	---	---	---	---	---	---
	27	86	159	16.6	81	158	15.5	76	157	14.3
	26	82	156	15.8	78	155	14.7	73	154	13.7
	24	77	151	14.5	72	150	13.5	68	149	12.7
	22	70	145	13.1	66	144	12.4	62	141	11.6
	20	63	137	11.7	59	135	11.1	55	131	10.5
2200	28	---	---	---	---	---	---	---	---	---
	27	83	157	15.4	79	156	14.4	74	155	13.5
	26	80	154	14.7	76	153	13.8	71	152	12.9
	24	73	148	13.4	69	147	12.6	65	145	11.9
	22	67	142	12.2	63	140	11.6	59	137	10.9
	20	60	133	11.0	56	131	10.5	53	127	10.0
2100	28	---	---	---	---	---	---	---	---	---
	27	79	154	14.4	75	153	13.5	70	151	12.6
	26	76	151	13.7	72	150	12.9	68	148	12.1
	24	70	145	12.5	66	144	11.9	62	141	11.2
	22	64	138	11.5	60	136	10.9	56	133	10.3
	20	57	130	10.4	54	127	9.9	50	123	9.4
2000	28	---	---	---	---	---	---	---	---	---
	27	76	150	13.4	71	149	12.6	67	147	11.9
	26	72	147	12.8	68	146	12.1	64	144	11.5
	24	67	141	11.9	63	140	11.2	59	137	10.6
	22	60	134	10.8	57	132	10.3	54	128	9.8
	20	54	126	9.9	51	123	9.4	48	117	9.0
	18	48	116	9.0	45	111	8.6	43	104	8.2

NOTE

- For best economy, operate at peak T.I.T.
- Power settings not approved for cruising are indicated by dashes.



Cruise Performance

Pressure Altitude 18,000 Feet

Conditions:

3100 Pounds

Recommended Lean Mixture

Cowl Flaps CLOSED

RPM	MP	20°C BELOW STANDARD TEMP -41°C			STANDARD TEMPERATURE -21°C			20°C ABOVE STANDARD TEMP -1°C		
		% MCP	KTAS	GPH	% MCP	KTAS	GPH	% MCP	KTAS	GPH
2400	28	---	---	---	---	---	---	---	---	---
	27	87	163	18.0	82	162	16.5	77	161	15.1
	26	84	160	16.9	79	159	15.5	74	158	14.3
	24	79	156	15.7	75	155	14.5	70	154	13.4
	22	73	151	14.2	69	150	13.2	65	147	12.4
	20	65	142	12.4	62	140	11.7	58	137	11.1
2300	28	---	---	---	---	---	---	---	---	---
	27	85	161	16.4	80	160	15.3	75	159	14.2
	26	81	158	15.6	77	157	14.5	72	156	13.5
	24	76	153	14.4	72	152	13.4	67	150	12.6
	22	70	147	13.1	66	146	12.3	62	143	11.6
	20	62	139	11.6	59	136	11.0	55	132	10.4
2200	28	---	---	---	---	---	---	---	---	---
	27	82	159	15.1	78	158	14.2	73	157	13.3
	26	79	156	14.5	75	155	13.6	70	154	12.8
	24	73	150	13.2	68	149	12.5	64	146	11.8
	22	66	143	12.1	62	141	11.4	59	138	10.8
	20	59	134	10.9	56	131	10.4	52	127	9.9
2100	28	---	---	---	---	---	---	---	---	---
	27	79	156	14.2	74	155	13.3	70	153	12.5
	26	76	153	13.6	71	152	12.8	67	150	12.0
	24	69	147	12.4	65	145	11.8	62	142	11.1
	22	63	140	11.4	60	137	10.8	56	134	10.3
	20	56	131	10.4	53	127	9.9	50	122	9.4
2000	28	---	---	---	---	---	---	---	---	---
	27	75	152	13.3	71	151	12.6	67	149	11.8
	26	72	149	12.8	68	148	12.1	64	145	11.4
	24	66	143	11.8	62	141	11.2	59	138	10.6
	22	60	136	10.8	57	133	10.3	53	129	9.8
	20	54	127	9.9	51	123	9.4	48	118	9.0
	18	48	117	9.0	45	112	8.6	43	103	8.2

NOTE

- For best economy, operate at peak T.I.T.
- Power settings not approved for cruising are indicated by dashes.

**CT182T**

Cruise Performance

Pressure Altitude 20,000 Feet

Conditions:

3100 Pounds

Recommended Lean Mixture

Cowl Flaps CLOSED

RPM	MP	20°C BELOW STANDARD TEMP -45°C			STANDARD TEMPERATURE -25°C			20°C ABOVE STANDARD TEMP -5°C		
		% MCP	KTAS	GPH	% MCP	KTAS	GPH	% MCP	KTAS	GPH
2400	28	---	---	---	---	---	---	---	---	---
	27	86	165	17.8	82	165	16.3	77	163	14.9
	26	83	162	16.7	78	162	15.4	73	160	14.2
	24	79	159	15.6	75	158	14.4	70	156	13.4
	22	73	153	14.2	69	152	13.2	65	149	12.4
	20	65	145	12.4	62	142	11.7	58	138	11.1
2300	28	---	---	---	---	---	---	---	---	---
	27	84	163	16.2	79	162	15.1	74	161	14.0
	26	81	160	15.4	76	159	14.3	71	158	13.4
	24	76	156	14.2	71	155	13.3	67	152	12.5
	22	70	150	13.0	66	148	12.2	62	144	11.5
	20	62	140	11.6	58	138	11.0	55	133	10.4
2200	28	---	---	---	---	---	---	---	---	---
	27	81	161	14.9	76	160	14.0	72	158	13.1
	26	78	158	14.3	74	157	13.4	69	155	12.6
	24	72	152	13.1	68	150	12.3	64	147	11.6
	22	65	145	11.9	62	142	11.3	58	138	10.7
	20	58	135	10.8	55	132	10.3	52	126	9.8
2100	28	---	---	---	---	---	---	---	---	---
	27	78	158	14.0	73	157	13.2	69	154	12.3
	26	75	155	13.4	71	154	12.6	66	151	11.9
	24	69	149	12.3	65	146	11.7	61	143	11.0
	22	63	141	11.3	59	139	10.8	56	134	10.2
	20	56	132	10.3	53	128	9.8	50	122	9.3
2000	28	---	---	---	---	---	---	---	---	---
	27	75	155	13.3	70	154	12.5	66	150	11.8
	26	72	152	12.7	68	150	12.0	64	147	11.4
	24	66	145	11.7	62	143	11.1	58	139	10.5
	22	60	137	10.8	57	134	10.3	53	130	9.8
	20	54	128	9.8	51	124	9.4	48	117	8.9
	18	48	118	9.0	46	112	8.6	43	103	8.2

NOTE

- For best economy, operate at peak T.I.T.
- Power settings not approved for cruising are indicated by dashes.